

B.E.G.**LUXOMAT®**

HF-MD1

94401 EAN: 4007529944019

230V high-frequency motion detector with 360° coverage and a range of up to Ø16m (200 m²)

Areas of application

- toilets
- equipment rooms

Order data

Designation	Colour	Art.No
HF-MD1	white	94401

Accessories

Designation	Colour	Art.No
RC-Arc extinction kit	white	10880
Mini-RC-Arc extinction kit		10882

Technical data

Voltage:	230 V AC +/- 10% 50 / 60 Hz
Dimensions:	101 x 42 x 42 mm
Power consumption:	approx. 1.2 W horizontal 360°
Detection area:	(Ceiling mounting) Ø 0.4 – 16 m
Range:	max. Ø 16 m towards
Monitored area (tangential movement):	200 m² / 2.5 m mounting height
Mounting height min./max./recommended:	1 m / 4 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Ambient temperature:	-15 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white mat, similar to RAL9010

Channel 1 (lighting control)

	1200 W, $\cos \varphi$ = 1
Switching power:	800 W LED max. inrush current I_p (20 ms) = 120 A
Type of contact (k):	1x μ -contact, NO contact
Follow-up time:	5 sec – 15 min
Switch-on threshold:	2 – 2000 Lux
Radar / HF technology:	5.8 GHz, < 10 mW

Product information

Microwave motion detector, designed for surface mount and installation in lights




Temperature-independent detection

Detection can be made through various materials

Range, switch-on threshold and follow-up time set via potentiometers

Application examples:

toilets, equipment rooms



Accessories



RC-Arc extinction kit

Art.No: 10880

Voltage: 230 V AC $\pm 10\%$

Dimensions: 38 x 12 x 26 mm

Degree / class of protection: IP20 / Class II



Mini-RC-Arc extinction kit

Art.No: 10882

Voltage: 230 V AC $\pm 10\%$

Dimensions: 50 x 23 x 8 mm

Degree / class of protection: IP20 / Class II