

**B.E.G. LUXOMATIC®**



**L7**

94451 EAN: 4007529944514

Round wall and ceiling light

Acrylic glass is suitable for all standard applications

Ideally supplements the HF-L7 and HF-L8

#### **Order data**

| <b>Designation</b> | <b>Colour</b> | <b>Art.No</b> |
|--------------------|---------------|---------------|
| L7                 | white         | 94451         |

## Technical data

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
| Voltage:                      | 230 V AC $\pm 10\%$ 50 / 60 Hz                       |
| Dimensions:                   | Ø 300 x 110 mm                                       |
| Lamp:                         | max. 23 W with bulb socket E 27                      |
| Photobiological safety:       | RG 0                                                 |
| Degree / class of protection: | IP40 / Class I                                       |
| Impact strength:              | 94446=IK02,<br>94451=IK06                            |
| Ambient temperature:          | -15 °C to +30 °C                                     |
| Housing:                      | <b>L8:</b> acrylic glass<br><b>L7:</b> Polycarbonate |
| Material color:               | white                                                |

## Product information

Round wall and ceiling light

Acrylic glass is suitable for all standard applications


Polycarbonate is appropriate for areas where greater impact resistance is required (e.g. schools, public buildings)

Ideally supplements the HF-L7 and HF-L8

Supply without lamp

### Application examples:

corridors, halls, staircases, storage rooms, cellars, toilets



| h (m) | Ø (m) | E (lx) |
|-------|-------|--------|
| 1.0   | 3.7   | 27     |
| 2.0   | 7.4   | 7      |
| 3.0   | 11.0  | 3      |
| 4.0   | 14.7  | 2      |
| 5.0   | 18.4  | 1      |

