B.E.G. LUXOMAT® net



PB6-KNX-ST

93176 EAN: 4007529931767

6-gang KNX wall-mounted push-button switch with LED status indicators for 60-mm flush-mount boxes, compatible with 55×55-mm switch series (64×64-mm adapter included).

Order data

Designation	Colour	Art.No
PB6-KNX-ST	white	93176

Technical data

Voltage:	via KNX BUS
Dimensions:	55 x 55 x 25 mm
Typ. power input:	9.5 mA (typ.) (Imax parameterisable 12.5 mA or 20 mA)
Degree / class of protection:	IP20 / Class III
Ambient temperature:	-5 °C to +45 °C
Material color:	white
Display elements:	(2-8) x LED (status; red, green, flashing)
Manual operation:	93172: 2 x Push button function 93174: 4 x Push button function 93176: 6 x Push button function 93178: 8 x Push button function
KNX TP 256:	Yes
Connections and wires:	2 x 1 mm pins for bus terminal plug board: 8 pin

Product information

Binary input device (multi-point pushbutton) for use in 60 mm flush-mounted boxes

Suitable for switch ranges 55x55

Adapter for switch ranges 64x64 included


Cover frame not included


User-friendly ETS interface

The following functions are possible:
- Switching
- Forced operation
- Percentage
- Temperature
- HVAC mode
- Dimming
- Blinds control
- Scene
- Edge function
- Counter

Settings ex ETS 4 for integration in KNX systems

The product database for import into the ETS database can be downloaded from the B.E.G. homepage.


64
55
11
14


+
-
KNX-Bus
-
+
KNX