

B.E.G.**LUXOMAT®**

PD2-S-SM Set 92152-92199

Slave PIR motion detector with 360° coverage
and a range of up to Ø10m (78 m²)

Order data

Designation	Colour	Art.No
PD2-S-SM	white	92152
Wire basket BSK (Ø 200 x 90 mm)	white	92199

Technical data

Voltage:	110 – 240 V AC 50 / 60 Hz
Dimensions:	Ø 200 x 90 mm (92199)
Power consumption:	approx. 0.2 W horizontal 360°
Detection area:	(Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Range:	
Monitored area (tangential movement):	78 m² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Impact strength:	IK09 (92199)
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant + coated steel basket (92199)
Material color:	white mat, similar to RAL9010
Pulse interval:	2 or 9 sec

Product information


Set : PD2-S-SM + Wire basket BSK (Ø 200 x 90 mm)
white

Slave device detector with circular detection area

For extending the detection area of a Master device

Trigger pulse to master device upon detected movement
independent of the ambient light level

Compatible with 230 V devices. Concerning exceptions please
see the respective master device.



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD2-S-SM

Art.No: 92152

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 98 x 50 mm

Power consumption: approx. 0.2 W



Wire basket BSK (Ø 200 x 90 mm)

Art.No: 92199

Dimensions: Ø 200 x 90 mm

Impact strength: IK09

Housing: coated steel basket