

**B.E.G.****LUXOMAT®**

## PD4-M-3C-TRIO-SM Set 92740-92386

230V 3-channel PIR motion detector with 360° detection and a range of up to Ø24m (450 m²), remote-controlled

### Order data

| Designation             | Colour | Art.No |
|-------------------------|--------|--------|
| PD4-M-3C-TRIO-SM        | white  | 92740  |
| Socket IP54 PD4-TRIO-SM | white  | 92386  |

### Areas of application

- open-plan offices
- conference rooms
- classrooms/seminar rooms

## Technical data

|                                           |                                                                                                                      |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Voltage:                                  | 110 – 240 V AC<br>50 / 60 Hz                                                                                         |
| Dimensions:                               | Ø 124 x 85 mm                                                                                                        |
| Power consumption:                        | approx. 0.5 W                                                                                                        |
| Detection area:                           | horizontal 360°<br>(Ceiling<br>mounting)<br>max. Ø 24 m<br>across<br>max. Ø 8 m<br>towards<br>max. Ø 6.4 m<br>seated |
| Range:                                    |                                                                                                                      |
| Monitored area (tangential<br>movement):  | 450 m² / 2.5 m<br>mounting<br>height                                                                                 |
| Mounting height<br>min./max./recommended: | 2 m / 10 m / 2.5<br>m                                                                                                |
| Degree / class of<br>protection:          | <b>IP54 (92386)</b>                                                                                                  |
| Impact strength:                          | IK04                                                                                                                 |
| Ambient temperature:                      | -25 °C to +50<br>°C                                                                                                  |
| Housing:                                  | polycarbonate,<br>UV-resistant                                                                                       |
| Material color:                           | white mat,<br>similar to<br>RAL9010                                                                                  |

### Channel 1 (lighting control)

|                      |                                                                                                                                                                                       |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Switching power:     | 3000 W, $\cos \varphi$<br>= 1<br>1500 VA, $\cos \varphi$<br>= 0.5<br>800 W LED<br>max. inrush<br>current $I_p$ (20<br>ms) = 165 A<br>max. inrush<br>current $I_p$ (200<br>µs) = 800 A |
| Type of contact (k): | 1x µ-contact,<br>NO contact with<br>tungsten pre-<br>make contact                                                                                                                     |
| Switch-on threshold: | 10 – 2000 Lux                                                                                                                                                                         |

### Channel 2 (lighting control potential-free (dry))

|                      |                                                                                                                                                                 |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Switching power:     | 3000 W, $\cos \varphi$<br>= 1<br>1500 VA, $\cos \varphi$<br>= 0.5<br>800 W LED<br>max. inrush<br>current $I_p$ (20<br>ms) = 165 A, $I_p$<br>(200 µs) = 800<br>A |
| Switch-on threshold: | 10 – 2000 Lux                                                                                                                                                   |

## Product information

Set : PD4-M-3C-TRIO-SM + Socket IP54 PD4-TRIO-SM  
white

Occupancy detector particularly for classrooms and training  
classrooms

Two contacts, one of them dry, for two groups of light,  
separate switching possible

One potential-free contact for blackboard illumination or HVAC

One common detection area

Two independent, movable light sensors

Manual switching possible via two or three pushbuttons

Version as master device

Detection area can be extended by using slave devices

Additional functions can be set up using the optional remote  
control.

Relay with tungsten pre-make contact, optimised for LED  
loads

Type of contact:

1x  $\mu$ -contact,  
dry NO contact  
with tungsten  
pre-make  
contact

**Channel 3 (HVAC  
control or lighting  
control, potential-free  
(dry))**

Switching power:

3000 W,  $\cos \varphi$   
= 1  
1500 VA,  $\cos \varphi$   
= 0.5  
800 W LED  
max. inrush  
current  $I_p$   
(20ms) = 120 A

Type of contact:

1x  $\mu$ -contact,  
dry NO contact




**Channel 1 to channel 3**

Follow-up time:

1 min – 90 min

Light measuring:

Mixed light  
measuring



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### **PD4-M-3C-TRIO-SM**

Art.No: 92740

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 124 x 85 mm

Power consumption: approx. 0.5 W



### **Socket IP54 PD4-TRIO-SM**

Art.No: 92386

Degree / class of protection: IP54

Housing: polycarbonate, UV-resistant

Material color: white