



PD4N-CAS Set 93474-93743-92199

CASAMBI-compatible PIR motion sensor with 360° detection and a range of up to Ø24m (450 m²)

Order data

Designation	Colour	Art.No
PD4N-CAS	white	93474
Corridor lens PD4N type A, Cover ring	black	93743
Wire basket BSK (Ø 200 x 90 mm)	white	92199

Technical data

Voltage:	230 V AC ±10% 50 Hz
Dimensions:	Ø 200 x 90 mm (92199)
Settings:	Casambi App
Power consumption:	0.5 W
Detection area:	horizontal 360° (Ceiling mounting) (93743)
Range:	max. Ø 40 m across max. Ø 20 m towards (93743)
Monitored area (tangential movement):	250 m² / 2.5 m mounting height (93743)
Mounting height min./max./recommended:	2.4 m / 2.6 m / 2.5 m (93743)
Degree / class of protection:	IP20 / Class II
Impact strength:	IK09 (92199)
Ambient temperature:	-5 °C to +45 °C
Housing:	polycarbonate, UV-resistant + coated steel basket (92199)
Material color:	black mat, similar to RAL9005 (93743)
Number of PIR sensors:	4
	Channel 1 (lighting control)
Follow-up time:	1 sec – 60 min
Brightness set value:	1 – 4000 Lux
Light measuring:	Mixed light measuring

Product information

Set : PD4N-CAS + Corridor lens PD4N type A, Cover ring black mat, similar to RAL9005 + Wire basket BSK (Ø 200 x 90 mm) white

Casambi-enabled occupancy detector

Bright LED indication for commissioning

Mixed light measurement with internal and external light sensor

Weighting between internal and external light sensor can be adapted to suit the application

Adjustment of the reflection factor and input of the luminosity for the display of the actual luminosity in the app

Extension of the detection area with additional B.E.G. Casambi devices possible

Individual adaption of detection sensitivity for each PIR sensor

Detection area can be restricted with blinds

Functions adjustable via Casambi app

Including pre-assembled spring clamp with strain relief and contact protection cap for recessed ceiling mounting

Accessory for surface mounting available

Accessories for wall mounting optionally available

Further accessories for colour matching optionally available



CASAMBI



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD4N-CAS

Art.No: 93474

Voltage: 230 V AC $\pm 10\%$ 50 Hz

Dimensions: $\varnothing$ 106 x 95 mm

Settings: Casambi App



Corridor lens PD4N type A, Cover ring


Art.No: 93743

Detection area: horizontal 360° (Ceiling mounting)

Range: max. $\varnothing$ 40 m across

max. $\varnothing$ 20 m towards

Monitored area (tangential movement): 250 m² / 2.5 m mounting height



Wire basket BSK ($\varnothing$ 200 x 90 mm)

Art.No: 92199

Dimensions: $\varnothing$ 200 x 90 mm

Impact strength: IK09

Housing: coated steel basket