



PD4N-CAS Set 93474-93788-92199

CASAMBI-compatible PIR motion sensor with 360° detection and a range of up to Ø24m (450 m²)

Order data

Designation	Colour	Art.No
PD4N-CAS	white	93474
SM socle mounting set IP54 PD4N H	black	93788
Wire basket BSK (Ø 200 x 90 mm)	white	92199

Technical data

Voltage:	230 V AC ±10% 50 Hz
Dimensions:	Ø 200 x 90 mm (92199)
Settings:	Casambi App
Power consumption:	0.5 W
Detection area:	horizontal 360° oval (Ceiling mounting) max. Ø 24 m across max. Ø 8 m towards max. Ø 6.4 m seated
Range:	
Monitored area (tangential movement):	450 m² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 10 m / 2.5 m
Degree / class of protection:	IP54 (93788)
Impact strength:	IK09 (92199)
Ambient temperature:	-5 °C to +45 °C polycarbonate, UV-resistant + coated steel basket (92199) black, similar to RAL9005 (93788)
Housing:	
Material color:	
Number of PIR sensors:	4
	Channel 1 (lighting control)
Follow-up time:	1 sec – 60 min
Brightness set value:	1 – 4000 Lux
Light measuring:	Mixed light measuring

Product information

Set : PD4N-CAS + SM socle mounting set IP54 PD4N
H black, similar to RAL9005 + Wire basket BSK (Ø
200 x 90 mm) white

Casambi-enabled occupancy detector

Bright LED indication for commissioning

Mixed light measurement with internal and external light
sensor

Weighting between internal and external light sensor can be
adapted to suit the application

Adjustment of the reflection factor and input of the luminosity
for the display of the actual luminosity in the app

Extension of the detection area with additional B.E.G. Casambi
devices possible

Individual adaption of detection sensitivity for each PIR sensor

Detection area can be restricted with blinds

Functions adjustable via Casambi app

Including pre-assembled spring clamp with strain relief and
contact protection cap for recessed ceiling mounting

Accessory for surface mounting available

Accessories for wall mounting optionally available

Further accessories for colour matching optionally available



CASAMBI



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD4N-CAS

Art.No: 93474


Voltage: 230 V AC $\pm 10\%$ 50 Hz
Dimensions: $\varnothing$ 106 x 95 mm
Settings: Casambi App



SM socle mounting set IP54 PD4N H

Art.No: 93788

Dimensions: $\varnothing$ 110 x 45 mm
Degree / class of protection: IP54
Material color: black, similar to RAL9005



Wire basket BSK ($\varnothing$ 200 x 90 mm)

Art.No: 92199

Dimensions: $\varnothing$ 200 x 90 mm
Impact strength: IK09
Housing: coated steel basket