

B.E.G.**LUXOMAT®**

PD9-M-1C-FC Set 92900-92993

230V PIR motion detector with 360° detection and a range of up to Ø10m (78 m²), remote-controlled

Order data

Designation	Colour	Art.No
PD9-M-1C-FC	white	92900
Square design frame PD9-FC	pure white	92993

Areas of application

- entrance halls
- small offices
- corridors/hallways

Technical data

Voltage:	110 – 240 V AC 50 / 60 Hz
	Sensor head: Ø 45 x 28 mm, Power supply: 165 x 24 x 24 mm + 45 x 45 x 2.6 mm (92993)
Dimensions:	
Power consumption:	approx. 0.5 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Range:	
Monitored area (tangential movement):	78 m² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Impact strength:	IK03
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	pure white mat, similar to RAL9010 (92993)
Cable length:	45 cm, screened

Channel 1 (lighting control)

	2300 W, cos φ = 1 1150 VA, cos φ = 0.5 800 W LED
Switching power:	max. inrush current I_p (20 ms) = 165 A max. inrush current I_p (200 μ s) = 800 A
Type of contact (k):	1x μ -contact, NO contact with tungsten pre- make contact
Follow-up time:	5 min – 30 min, Pulse
Switch-on threshold:	20 – 1000 Lux
Light measuring:	Mixed light measuring

Product information

Set : PD9-M-1C-FC + Square design frame PD9-FC
pure white mat, similar to RAL9010

Mini-occupancy detector

One channel for light switching

Version as master device

Detection area can be extended by using slave devices

Easy operation with remote control (required)




Manual switching via push-button possible

Power supply passes through the hole in the ceiling for the
detector (34 mm Ø)

Spring clips for quick and easy installation in suspended
ceilings and light fittings

Includes 45 mm cover ring and blinds

Factory settings 10 min and 500 lux



Set items

To receive the bundle according to the technical specification, please order the items listed.




PD9-M-1C-FC

Art.No: 92900

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Sensor head: Ø 45 x 28 mm, Power supply: 165 x 24 x 24 mm

Power consumption: approx. 0.5 W



Square design frame PD9-FC

Art.No: 92993

Dimensions: 45 x 45 x 2.6 mm

Housing: polycarbonate, UV-resistant

Material color: pure white mat, similar to RAL9010