

B.E.G.**LUXOMAT®**

PD9-S-SDB-FC Set 92915-92238

Slave PIR motion detector with 360° coverage
and a range of up to Ø10m (78 m²), IP65

Order data



Designation	Colour	Art.No
PD9-S-SDB-FC	white	92915
Cover ring PD9 Ø 36 mm	white	92238

Technical data

Dimensions:	Ø 36 x 28 mm
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Range:	
Monitored area (tangential movement):	78 m² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP65 / Class III
Impact strength:	IK03
Material color:	white glossy (92238)
Cable length:	350 cm

Product information

Set : PD9-S-SDB-FC + Cover ring PD9 Ø 36 mm white glossy



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD9-S-SDB-FC

Art.No: 92915

Dimensions: Ø 36 x 28 mm

Detection area: horizontal 360° (Ceiling mounting)

Range: max. Ø 10 m across

max. Ø 6 m towards

max. Ø 4 m seated



Cover ring PD9 Ø 36 mm

Art.No: 92238

Dimensions: Ø 36 mm

Housing: polycarbonate, UV-resistant

Material color: white glossy