B.E.G. LUXOMAT®



PICO-S-FC

92700 EAN: 4007529927005

Slave PIR motion detector with 360° coverage and a range of up to Ø10m (78 m²), IP65

Order data

Designation	Colour	Art.No
PICO-S-FC	white	92700

Technical data

Voltage:	110 – 240 V AC 50 / 60 Hz
Dimensions:	Ø 33 x 60 mm
Power consumption:	approx. 0.3 W
Detection area:	horizontal 360° (Ceiling mounting)
Range:	max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Monitored area (tangential movement):	78 m² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP65 / Class II
Impact strength:	IK04
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white mat, similar to RAL9010
Cable length:	130 cm
Pulse interval:	9 sec

Product information

Mini Slave device without additional power unit for connection to master device


Suitable for high-humidity locations


Trigger pulse to master device upon detected movement independent of the ambient light level


Compatible with 230 V devices. Concerning exceptions please see the respective master device.

Mounting with clip ring (included) for lights or with spring clips for suspended ceilings

Typical applications:
offices, conference rooms, hospitals, galleries, nursery schools


cable
45
15
33
26


h=2.5m
ø 4m
ø 6m
ø 10m


L
N
S
N
L
L'
C1
Master
R
N
L
Slave